

Enterprise Level

## POWERPLATINUM

Salient's PowerPlatinum is a 2U rack-mount NVR designed to handle the most demanding IP video surveillance requirements utilizing highly scalable and extended storage options, maximum I/O throughput, and robust processing capability, making it ideally suited for intensive digital video processing. Tailor your enterprise video requirements with the PowerPlatinum's offering of high performance CPU power, 96GB memory, hot-swappable hard drives and dual redundant hot-plug power supplies.

### FEATURES

- Record, live view, playback, archive video
- Rack mount 2U form factor
- Front access with locking bezel for hotswap



# POWERPLATINUM

## SYSTEM SPECS

Operating System	Windows Server 2019 Standard Embedded
Processor	Single Intel Xeon
Memory	96GB
Network	Dual Port 10GbE BASE-T & Dual Port 1GbE BASE-T
Hybrid Capable	IP only
IP Camera Support	Yes
Hard Drive (OS)	2 - 480GB SSD in RAID1 configuration
Hard Drive (Video Storage)	Up to 192TB
RAID Controller	Yes
RAID Level of Storage	5 or 6
# of Hot Spares Supported	1 or 2

Graphics Adapter	Integrated
Max Resolution	1920x1200
Video Display Ports	1 VGA (front), 1 VGA (rear)
USB Ports	2 USB 2.0 (front), 2 USB 3.0 (rear)
Other Ports	1 serial port (rear)
PCIe Slots	2x FHFL x8, 1x FHHL, 1x LPHL
Optical Drive	Optional external USB attached DVD-RW
Accessories	Keyboard, mouse & rail kit included
TPM Support	Yes
Life Cycle Controller	iDRAC 9
Life Cycle Controller Software	ACIA - iDRAC Enterprise software license for PowerUltra or PowerPlus with iDRAC V9
DAS Support	Yes - PERC RAID controller required. Part number ACDB. Requires 1 PCI-E slot

## CHASSIS FEATURES

Form Factor	2RU Rackmount
Height	3.42 inches (86.8 mm)
Width	18.98 inches (482.0 mm)
Depth	28.17 inches (715.5 mm)
Weight	72.91 lbs (33.1kg)

## WARRANTY

3 and 5 year (basic, NBD, or 4HR)

Company and product names mentioned are registered trademarks of their respective owners. Salient Systems reserves the right to change specifications without prior notice. Copyright Salient Systems. 6/2021

## OPERATING ENVIRONMENT

Operating Temp.	50°F - 95°F (10°C - 35°C)
Power Supply	Dual 750W - 100 to 240VAC auto ranging and redundant
Relative Humidity	
Operating:	10% - 80% non-condensing Max dew point 84.2°F
Storage:	5% - 95% non-condensing Max dew point 91°F
BTU	2891 BTU/hr

