

**NOTICE:** The RED3 Integrated Server is being discontinued. Last date for orders is December 31, 2021. Salient will continue to support the RED3 IS until September 30, 2024. If you have questions, please contact your Salient sales representative or contact us on our website.

# RED3 INTEGRATED SERVER 24PORT

Salient's RED3 IS (Integrated Server) combines client, server and switch for professional video surveillance deployments. The RED3 IS all-in one unit provides high performance, featuring Intel Core i5 processors for HD and 4K resolution recording at high frame rates. The RED3 IS's built-in PoE switch features 24 ports of PoE or PoE+ connectivity, 2 Combo 1GB uplink ports and a power capacity of up to 487 watts. RED3 IS has full compatibility with HDMI and VGA connectors allowing up to 4K resolution monitor output. Up to 48TB of storage capacity provides longer term video retention requirements. RED3 IS includes 24 channels of CompleteView Pro VMS software fully licensed, a 3 year warranty and 3 years of CompleteView software updates. With the RED3 IS, just add cameras for a fully capable, professional class video surveillance solution.

## OVERVIEW

CPU	Intel Core i5
Memory	8GB
Storage	2TB - 48TB
Windows OS	Windows 10 IoT
# of Channels	24



24Port



# RED3 IS 24PORT

## SYSTEM SPECS

Operating System	Windows 10 IoT
Processor	Intel Core i5
Memory	8GB
Hybrid Capable	No
IP Camera Support	Yes
Hard Drive (OS)	120GB SSD
Hard Drive (Video Storage)	Up to 48TB
Graphics Adapter	Integrated
Max Resolution	3840x2160

Video Display Ports	HDMI and VGA
USB Ports	2 front (3.0), 2 rear (3.0)
Other Ports	eSATA rear
Optical Drive	N/A
Accessories	Keyboard, mouse & mounting brackets included
TPM Support	No
PoE Ports	24 x 10/100
Total PoE Output	487W (Class 3 PoE on each port)
Uplinks	2 x 1Gbps Combo SFP/Ethernet ports
Intelligent Switch Control	Browser based
Supports On-board Video Client	Yes

## CHASSIS FEATURES

Form Factor	1RU Rackmount
Height	1.75 inches (44.5 mm)
Width	17.25 inches (438.2 mm)
Depth	21.2 inches (538.5 mm)
Weight	30 lbs (13.6kg) max

## OPERATING ENVIRONMENT

Operating Temp.	32°F - 104°F (0°C - 40°C)
Power Supply	750W
Relative Humidity	10% to 90% non-condensing
BTU	594

## WARRANTY

3 year basic

Company and product names mentioned are registered trademarks of their respective owners. Salient Systems reserves the right to change specifications without prior notice. Copyright Salient Systems. 6/2021

