

Salient Systems
4616 W. Howard Lane
Building 1, Suite 100
Austin, TX 78728
512-617-4800
512-617-4801 FAX
www.salientsys.com

February 2017

Product Guide Specification

Specifier Notes: This product guide specification is written according to the Construction Specifications Institute (CSI) 3-Part Format, based on *MasterFormat 2004* and *The Project Resource Manual—CSI Manual of Practice*. *The Manufacturer is responsible for technical accuracy. By removing the references to specific Salient Systems product names or part numbers, the text may also be used also in performance-based specifications.*

The section must be carefully reviewed and edited by the Architect or Engineer to meet the requirements of the project and local building code. *Italicized Words and sentences within brackets [] are choices to include or exclude a particular item or statement.* Coordinate this section with other specification sections and the Drawings.

Section 28 23 23 Video Surveillance Systems Infrastructure

PART 1 – GENERAL

1.1 SUMMARY

A. Section Includes

1. Video surveillance servers.

B. Related Sections

1. Section 28 23 13 – Video Surveillance Control and Management Systems.
2. Section 28 23 16 – Video Surveillance Monitoring and Supervisory Interfaces.
3. Section 28 23 19 – Digital Video Recorders and Analog Recording Devices.
4. Section 28 23 29 – Video Surveillance Remote Devices and Sensors

1.2 REFERENCES

- A. Underwriters Laboratories, Inc. (UL) (www.ul.com)
 - 1. UL 50 Enclosures for Electrical Equipment.
 - 2. UL 60950-1 Information Technology Equipment - Safety.

1.3 SUBMITTALS

- A. Submit under provisions of Section [01 33 00].
- B. Product Data:
 - 1. Manufacturer's data, user and installation manuals for all equipment and software programs including computer equipment and other equipment required for a complete VMS.
- C. Shop Drawings
 - 1. System device locations on architectural floor plans.
 - 2. Full Schematic of system including wiring information for all devices.
- D. Closeout Submittals
 - 1. User Manuals
 - 2. Parts list.
 - 3. System device locations on architectural floor plans.
 - 4. Wiring and connection diagrams.
 - 5. Maintenance requirements.

1.4 QUALITY ASSURANCE

- A. Manufacturer shall have a minimum of 10 years experience in the manufacture and design of VMS products.
- B. Installer:
 - 1. Minimum of 5 years experience installing VMS products.
 - 2. All installation, configuration, setup, program and related work shall be performed by technicians thoroughly trained by the manufacturer in the installation and service of the equipment provided.

1.5 DELIVERY, STORAGE AND HANDLING

- A. Comply with requirements of Section [01 60 00].
- B. Deliver materials in manufacture's original, unopened, undamaged containers with original identification labels.
- C. Protect stored materials from environmental and temperature conditions following the manufacturer's instructions.
- D. Handle and operate products and systems according to manufacturer's instructions.

1.6 WARRANTY

- A. Provide manufacturer's warranty covering three (3) years for replacement and repair of defective equipment.

1.7 MAINTENANCE

- A. Make ordering of new equipment for expansions, replacements and spare parts available.
- B. Provide factory direct technical support to the installing firm.

PART 2 – PRODUCTS

2.1 VIDEO SERVER

- A. Manufacturer:
The Video Server shall be the PowerChoice as supplied by:
Salient Systems Corporation
4616 W. Howard Lane, Building 1, Suite 100
Austin, TX 78728
512-617-4800
512-617-4801 FAX
www.salientsys.com
- B. Substitutions:
Under the provisions of Division 1:
 - 1. All proposed substitutions must be approved by the Consultant or Architect/Engineer professional.

2. Proposed substitutions must provide a line-by-line compliance document.

C. General Server Features:

1. The video server shall be integrated into a workstation-class computing platform ('PC').
2. The server Operating System shall be Microsoft Windows 7 64 bit Professional.
3. Server shall have two front accessible USB ports.

D. Server System Components:

1. The server shall meet or exceed the following system component specifications:
 - a. Server shall utilize a Intel H81 Chipset
 - b. Server shall utilize Intel Core i3-4160 \geq 3.60GHz
 - c. Server shall have at least 4GB of system memory
 - d. Server Storage Controller shall be SATA (serial ATA) ports – JBOD
 - e. Server hard drives shall be Surveillance Class hard drives
 - f. Server shall provide between 1TB and 6TB of internal storage for video event data
 - g. Server shall have DVD-R/W internal DVD recordable drive
 - h. Server shall have one Gigabit Ethernet Network controller port
 - i. Server shall have Intel Integrated Graphics adaptor.
 - j. Server shall have 6 USB 2.0 and 2 High Speed USB 3.0 serial ports, for the attachment of external storage, digital I/O and archive devices.
2. The server shall provide the following optional components:
 - a. Using analog frame grabber technology, the DVMS shall be capable of supporting between zero (0) and sixteen (32) NTSC or PAL video sources, in increments of four (4) video sources.
 - b. Using digital video capture technology, the DVMS shall be capable of supporting IP-based video sources, in increments of one (1) video source.
 - c. The DVMS server shall support the following "Compression Formats" for analog video sources (NTSC or PAL):
 1. MJPEG
 2. MPEG4
 3. H.264
 - d. The video frame grabber expansion board shall utilize a separate video decoder for each video source, allowing for fully independent control of the following for each source:
 1. Brightness;
 2. Contrast;
 3. Hue;

4. Saturation;
5. Chroma.
- e. The server shall optionally provide support for between sixteen (16) and one-hundred (100) digital input and output points for wired integration with access control, building automation equipment, sensors, monitors, or other application requirements that may be determined at a later time. The server shall support any combination of the following digital input and output devices that are physically connected to the server via the PC's USB bus:
 1. 8in + 8 out – 8 optically isolated digital inputs and 8 reed-relay outputs.
 2. 16 in – 16 optically isolated digital inputs.
 3. 16 out – 16 reed-relay outputs.
 4. 48 TTL – 48 TTL points defined as inputs or outputs in blocks of 8.
 5. 96 TTL – 96 TTL points defined as inputs or outputs in blocks of 8.
3. The server shall support capture of video from cameras:
 - a. Server shall support any analog camera, NTSC or PAL, directly connected to optional analog frame grabber expansion board.
 - b. Server shall support IP cameras from leading camera manufacturers, with these video feeds connected through the server network controller without the need for encoders or other devices:
 1. ACTi
 2. American Dynamics
 3. Appro
 4. Arecont Vision
 5. Axis
 6. Basler
 7. Bosch
 8. Canon
 9. IQinVision
 10. Lumenera
 11. Panasonic
 12. Pelco
 13. Samsung
 14. SmarterCam
 15. Sony
 16. Toshiba
 - c. Server shall support control of PTZ camera (analog or IP) from leading camera manufacturers:
 1. ACTi
 2. American Dynamics ASCII

Salient Systems PowerChoice Video Server Specification

3. Axis
4. Bosch
5. Canon VCC-4
6. Kalatel
7. Panasonic: conventional and new (analog)
8. Panasonic IP
9. Pelco: ASCII, D, P (analog)
10. Pelco IP
11. Philips BiPhase
12. RVision
13. SAE
14. Samsung
15. Sensormatic
16. Sony EVI –D30/D31
17. Sony P5 IP
18. Sony Visca IP
19. Toshiba IK-WB IP
20. Toshiba IK-WB21A IP
21. Ultrak
22. VCL
23. Vicon

E. Chassis Features:

1. The chassis shall be a Micro Tower form factor.
2. The dimensions shall be 14.2” x 6.9” x 16.4”
3. Front ports shall be 2x USB.
4. Cooling shall be 1x 80mm Internal Fans

F. Electrical:

1. Input Voltage: AC 90-264V
2. Power Supply: 290W AC

G. Environmental:

1. Temperature Range:
 - a. Operating: 32 to 95 degrees F (0 to 35 degrees C)
 - b. Non-Operating: -40 to 149 degrees F (-40 to 65 C)
2. Relative Humidity Range:
 - a. Operating 20 – 80% (non condensing at ambient)

PART 3 – EXECUTION

3.1 EXAMINATION

- A. Examine area to receive devices and notify any adverse conditions affecting installation or subsequent operation.
- B. Do not begin installation until unacceptable conditions are corrected.

3.2 PREPARATION

- A. Protect devices from damage during construction.

3.3 INSTALLATION

- A. Install devices in accordance with manufacturer's instruction at locations indicated on the floor drawing plans.
- B. Perform installation with qualified service personnel.
- C. Install devices in accordance with the National Electrical Code or applicable local codes.
- C. Ensure selected location is secure and offers protection from accidental damage.

3.4 FIELD QUALITY CONTROL

- A. Test snugness of mounting screws of all installed equipment.
- B. Test proper operation of all VMS devices.
- C. Determine and report all problems to the manufacturer's customer service department.

3.5 ADJUSTING

- A. Make proper adjustment to video system devices for correct operation in accordance with manufacturer's instructions.

3.6 DEMONSTRATION

- A. Demonstrate at final inspection that the VMS is functioning properly.

END OF SECTION